# zapp

### CONTACT

Zapp Precision Metals GmbH HIGH PERFORMANCE ALLOYS Zapp-Platz 1 40880 Ratingen | Germany Phone +49 2102 710-204 highperformancealloys@zapp.com www.zapp.com



Further information regarding our products and locations are available in our image brochure and under www.zapp.com. The illustrations, drawings, dimensional and weight data and other information included in this flyer are intended only for the purposes of describing our products and represent non-binding average values. They do not constitute quality data, nor can they be used as the basis for any guarantee of quality or durability. The applications presented serve only as illustrations and can be construed neither as quality data nor as a guarantee in relation to the suitability of the material. This cannot substitute for comprehensive consultation on the selection of our products and on their use in a specific application. The flyer is not subject to change control. Revision: November 2023

### Zapp is certified to ISO 9001 and AS 9120

## OUR NEW STOCKING PROGRAM C-22<sup>®</sup> PIPES & TUBES



C22\_PT/E/11.2023

### ALLOY C-22<sup>®</sup> | 2.4602 | UNS N06022

- ESR (electro slag remelted) for optimized corrosion resistance and processing
- Produced in accordance with ASTM B619 CI.I or II/ ASME SB619; ASTM B-626 CI. III/ASME SB 626, NACE MR 0175/ISO 15156, NACE MR 0103/ISO 17945
- Third party inspection certification 3.1C/3.2 according to VdTÜV data sheet 479 and AD 2000-W2/W10 on request
- O Express shipments within 24h possible



### C-22<sup>®</sup>-2.4602 PIPE AND TUBE

(dimensions in mm)

Outside diameter\*

Wall thickness\*

welded	welded		
6.35	0.89		
8.00	1.20		
10.00	1.00	2.00	
12.00	1.00	2.00	
13.72	1.65	2.24	
17.15	1.65	2.31	
19.05	1.65		
21.34	1.65	2.11	2.77
25.00	2.00		
25.40	1.65	2.11	
26.67	2.11	2.87	
33.40	2.77	3.38	
42.40	2.77		
48.26	2.77	3.68	
60.30	2.77	3.91	
73.03	5.16		
76.20	3.05		
88.90	3.05	5.49	
114.30	3.05	6.02	
168.30	3.40	7.11	
219.10	3.76	8.18	
seamless	seamless		
33.40	4.55		
48.26	5.08		
60.30	3.91	5.54	
88.90	5.49	7.62	
114.30	8.56		

\*other dimensions and alloys on request